

30 JUN 2025



BST Eltromat France
Impasse de la Noisette – CE402
F-91374 Verrières Le Buisson cedex

T +33 1 69 20 07 41
bstfrance@bst.group · www.bst-france.fr

BST Eltromat France · Impasse de la Noisette – CE402 · F-91374 Verrières Le Buisson cedex

ETILABEL

Voie du Verger

27100 VAL DE REUIL

France

Quotation no: AQ2508976 - 00

Date: 25/06/2025

Subject:
ETILABEL_TradeIN_ASO057392_40.
1168

Page: 1 / 5

Contact-No.	ACU230006	BST Sales	
Contact		Contact	Tondu, David
Phone		Phone	+33 169 200741
Email		Email	David.Tondu@bst.group

We thank you for your inquiry.

Offer according to the following application parameters:

Machine:	ABG rewinder
Max. web width:	330 mm
Max. speed:	350 m/min

Item	Quantity	Description	Price
10	1	TubeScan Print Inspection System The TubeScan is designed as an optical quality assurance system to be used in high quality printing. The intelligent combination of imaging technology and the strobe principle allows a simple and reliable quality check during printing or finishing. The system consists of a modular designed, highly integrated PC system and a digital camera unit. High-level camera technology and advanced operating elements are used together with the latest microelectronics. TubeScan is available in the variants digital strobe, digital strobe XL and eagle view, which include the following functions:	19.295,40 € incl. 30% Discount
	1	TubeScan Digital Strobe 330 Web Viewing System for web width < 330 mm including: • TubeScan Image Capture System with digital camera • high power LED illumination • power supply 100V - 240V, 50/60Hz • friction wheel encoder with spring load bracket and cable • TubeScan Digital Strobe software	

Item	Quantity	Description	Price																						
		• menu guided graphic GUI for intuitive touch operation • automatic repeat synchronization by reference image • no additional print mark sensor required • 1 Touch monitor for operation • 1 Full HD monitor for high-speed web viewing • 1 Desktop PC with Intel CPU with Windows 10 (64 bit operating system)																							
		System:																							
1		Operating mode Fine Inspection (Digital Strobe++) Upgrade of a TubeScan web monitoring system to a TubeScan++ inspection system • detection of missing labels and fine print inspection for small defect sizes featuring: • job management • multi-zone processing (adjustable inspection sensitivity) • masking function • auto matrix detection • selectable 'averaging' mode • fine-text algorithm • inspection on up to 20 lanes with adjustable width • individual defect counter per lane • global repeat and defect counter • generation of binary defect output upon finding a defect (150 mA, 0 V low, +24 V high)																							
1		'Turbo Speed' extension Speed extensions for applications with higher web speeds or performance requirements based on HS cameras and 4k graphics adapters																							
1		Power cord EU Power cord with plug type for EU.																							
		Camera unit 1:																							
1		Technical Information <table><tr><td>TubeScan:</td><td>DS 330</td></tr><tr><td>Camera width:</td><td>410 mm</td></tr><tr><td>Camera height:</td><td>290 mm</td></tr><tr><td>Inspection width:</td><td>330 mm</td></tr><tr><td>extended to:</td><td>without extension</td></tr><tr><td>Max. inspection speed:</td><td>400 m/min</td></tr><tr><td>Speed level:</td><td>Turbo Speed extension</td></tr><tr><td>Camera type:</td><td>4000 px option</td></tr><tr><td>System resolution:</td><td>0.0833 mm/px</td></tr><tr><td>Defect size in homogeneous areas:</td><td>0.03 mm²</td></tr><tr><td>Defect size in structured areas:</td><td>0.06 mm²</td></tr></table>	TubeScan:	DS 330	Camera width:	410 mm	Camera height:	290 mm	Inspection width:	330 mm	extended to:	without extension	Max. inspection speed:	400 m/min	Speed level:	Turbo Speed extension	Camera type:	4000 px option	System resolution:	0.0833 mm/px	Defect size in homogeneous areas:	0.03 mm ²	Defect size in structured areas:	0.06 mm ²	
TubeScan:	DS 330																								
Camera width:	410 mm																								
Camera height:	290 mm																								
Inspection width:	330 mm																								
extended to:	without extension																								
Max. inspection speed:	400 m/min																								
Speed level:	Turbo Speed extension																								
Camera type:	4000 px option																								
System resolution:	0.0833 mm/px																								
Defect size in homogeneous areas:	0.03 mm ²																								
Defect size in structured areas:	0.06 mm ²																								
1		Camera type 4000 Camera option with higher resolution using 2 cameras (4000 Pixel)																							
1		Roll Guided Backing Bar for TubeScan DS 330 & 370																							

Item	Quantity	Description	Price
		Backing bar with rotating support rollers for sensitive materials including black / white acrylic contrast plate.	
		Note: The material web may wrap around the rollers by max. 3°	
1		Mounting brackets customer-provided The mounting brackets or machine adaptations required for mounting the camera housing are provided by the customer.	
		User interface:	
1		Operator Monitor 22" Multitouch monitor for intuitive operation	
1		Extension Cable Set 5 m Extension of the video, touch and power supply cables to a total of 5 m consisting of: • 2 x 5 m HDMI cable to the operating and viewing monitor • 1 x 3 m USB cable to the operating monitor • 2 x 3 m extension power supply cable to the operating and viewing monitor • 1 x 3 m extension cable DC jack for the power supply of the TubeScan	
1		View monitor 22" Parallel display of the live image and found defects on an additional viewing monitor	
		Functions:	
1		Placement Queue for Rewinder • rewriter control via SlowDown / FinalStop or DefectFound signals • configurable delay distances • defect queue with speed adaptation Please note: Rewinder must be prepared for signal transmission (slow-down and final stop) as well as sufficient stopping distance between camera unit and stop position (e.g. splicing table).	
1		Placement Queue Cable from V10 Controller Board and higher versions (06/2019 SN 40.xxxx)	
		Documentation / Manual:	
1		Document type CD and User Manual User manual including assembly and maintenance instructions on CD-ROM and in printed edition.	
		You can also find all documentation in other languages as well as additional information at https://bst.help/s/tubescan .	
1		1st Language English	
1		1 Trade-In System Trade-In for TubeScan legacy system: 40.1168 • 30% Trade-in discount on the reconfigured TubeScan DS including options with the exception of customization-intensive modules like e.g. QLink-Workflow, Variable Data or Dynamic Job Change. There will be a Trade-In trade-in fee of 800 € will be charged. • All active TubeScan DS without age limit are eligible for a tradein. •	

Item	Quantity	Description	Price
		The customer undertakes to return the legacy system at its own expense back to BST GmbH or to the local BST branch. BST GmbH will recycle the Legacy System free of charge and to dispose it in accordance with the applicable environmental regulations.	
		Current lead time 5-7 weeks Subject to technical clarification	
		Warranty period 12 months The warranty period is regulated in our general terms and conditions. The warranty period begins with the delivery of the product (passing of risk), not after commissioning.	
		Total	27.564,86 €
		less 30% Discount	8.269,46 €
		Total net	19.295,40 €

Commissioning:

The mentioned total price does not include installation and start-up on site. These services can be offered upon request.

Delivery conditions:

CPT Carriage Paid To (Incoterms 2020)

Freight and packaging excluded

Terms of payment:

(individual payment conditions)

40% at order time, 60% at 45 days of invoicing

This quotation expires on:

25/09/2025

Our deliveries and services are based on our general Terms and Conditions.

In particular we refer to the reservation of property in all its forms.

Our general Terms and Conditions are available on our homepage

<https://www.bst.elexis.group/en/global/general-terms-and-conditions>.

Attention: Deliveries from these goods/products, software, technologies into other countries (e.g. embargo affected countries) or other receivers can be subject to authorization or can be prohibited. We refer to the current Embargo restriction of the European Union.

Info: Germany: www.bafa.de

The Customer warrants that the supplied goods will not be (re-)exported to or for the use in Russia or Belarus. If the Customer (re-)exports the supplied goods to or for the use in Russia or Belarus, the Seller has the right to terminate the contract with immediate effect and will notify the competent authorities of the respective breach.

Kind regards

BST eltromat France

Quotation no: AQ2508976-00

Subject: ETILABEL_TradeIN_ASO057392_40.1168

Date: 25/06/2025

Page: 5 / 5



an **elexis** company

Signature

A handwritten signature in blue ink, consisting of a series of loops and strokes.

25/06/2025 14:37

IVO
30 JUN 2025



